

STANDING RIGGING

- 1- Headstay - 7/32" 1x19 s/s x 37'9", 1/2" & 7/16" Marine Eyes
- 1- Backstay - 3/16" 1x19 s/s x 31'7½", 3/8" Marine Eye & Fork with 5/16" hole
- 2- Bridles - 5/32" 1x19 s/s x 8'0-3/4", 1/4" Thd. Shank & Fork with 1/4" hole
- 1- Boom Lift - 1/8" 7x19 s/s x 3'6", 1¼" Nico Loop & Nico Snap Hook
- 2- Uppers - 3/16" 1x19 s/s x 36'1½", 3/8" Thd. Shank & Fork with 5/16" hole
- 2- Fwd. Lowers - 5/32" 1x19 s/s x 17'4½", 1/4" Thd. Shank & Fork with 1/4" hole
- 2- Aft. Lowers - 5/32" 1x19 s/s x 17'6-3/4", 1/4" Thd. Shank & Fork with 1/4" hole
- 2- Lifelines - 1/8" 1x19 s/s Plastic Coat x 28'4¼", 1/4" Thd. Shank & Fork with Pelican Hook

NOTE:

- 1) All dimensions are center eye to eye or end of Thd. Shank.
- 2) On Insulated Backstays, keep insulators as far apart as possible and the lower insulator above the Backstay Bridle Plate.

RUNNING RIGGING

- 1- Main Halyard - All Wire 1/8" 7x19 s/s x 69'7" Wire Rope
- 1- Main Halyard - Standard 1/8" 7x19 s/s x 34'8" Wire Rope
- 1- Jib Halyard - Standard 5/32" 7x19 s/s x 37'3"
For cabin top = 48', one end open.
- 2- Halyard Tails - Standard 5/16" x 38' Dacron Yacht Braid
- 1- Main Sheet - Standard 3/8" x 80' Dacron Yacht Braid
- 2- Genoa Sheets - Standard 7/16" x 45' Dacron Yacht Braid
- 1- Down Haul - Standard 1/4" x 6' Dacron Yacht Braid
- 1- Out Haul - Standard 1/8" x 4' Dacron Yacht Braid

SPINNAKER GEAR

- 1- Spinnaker Halyard - 3/8" x 90' Dacron Yacht Braid
- 2- Spinnaker Sheets - 3/8" x 45' Dacron Yacht Braid
- 1- Topping Lift - 3/8" x 60' Dacron Yacht Braid
- 1- Fore Guy - 3/8" x 38' Dacron Yacht Braid