

Bridge

Model	Year Intro	LOA	LWL	Beam	Draft	Displacement	Ballast	Sail Area	PHRF	Clearance	I	J	P	E	LP
Cal 20	1961	20' 0"	18' 0"	7' 0"	3' 4"	1950	900	196							
Cal 24		24' 4"	20' 0"	8' 0"	4' 3"	3300	1400	260			29' 9"	9' 4"	25' 9"	9' 6"	
Cal 24 T/4		24' 1.5"	21' 0"	8' 0"	4' 0"	4000	2000	256							
Cal 25		25' 0"	20' 0"	8' 0"	4' 0"	4000	1700	286							
Cal 27		27' 4.5"	22' 4"	9' 0"	4' 6"	5400	2500	350			34'	11' 10"	28' 8"	9' 7"	20' 5"
Cal 2-27		26' 7"	22' 1"	9' 3"	4' 3"	6700	3100	371			36'	12'	30.8'	10.3'	
Cal 27 MIII		26' 8"	23' 3"	9' 0"	5' 0"	5200	2000	335.5							
Cal 3-27		26' 8"	23' 3"	9' 0"	5' 0"	5200	2000	335.5							
Cal 29, 2-29		29' 0"	24' 0"	9' 3"	4' 6"	8000	3350	434							
Cal 30		30' 0"	24' 5"	10' 0"	4' 6"	8200	2550	420							
Cal 2-30		30' 8"	25' 0"	9' 0"	5' 0"	10300	4500		180		37'	12.33'	35'	13.5'	
Cal 3-30		30' 1.5"	26' 4.5"	10' 2"	5' 6"	10500	5000	474							
Cal 31		31' 6"	25' 8"	10' 0"	5' 0"	9170	3600	490		45' 5"					
Cal 33, 33-2		33' 0"	27' 6"	11' 4"	6' 4"	10800	4475	585		50' 3"					
Cal 2-34		33' 3"	26' 0"	10' 0"	5' 0"	9500	3750	515							
Cal 35		35' 1"	28' 9"	11' 0"	4' 8"	15000	5000	546							
Cal 39 Shoal		39' 0"	32' 1"	12' 0"	5' 6"	19000		720/776.6	114						
Cal 39 Deep		39' 0"	32' 1"	12' 0"	6' 8"	17000/19000	7000		106						
Cal 40		39' 6"	30' 6"	11' 0"	5' 6"	15500	6000				46'	15' 1"	40'	17' 5"	
Cal 43		42' 8"	32' 6"	11' 6"	6' 6"	23000	8000	885			52.5'	16.9'	44.8'	17.6'	
Cal 44 Deep		43' 6"	36' 3"	13' 6"	6' 5"	25000	10000	860.3							
Cal 44 Shoal		43' 6"	36' 3"	13' 6"	5' 5"	25000	10000	860.3							
Cal 2-46 Sloop		45' 6"	37' 6"	12' 6"	5' 0"	30000	8000	784							
Cal 2-46 Ketch		45' 6"	37' 6"	12' 6"	5' 0"	30000	8000	864							